USSN 10/615,168 Group No. 3632

Examiner: Marsh, Steven M.

Page 4

## **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions and listings of claims in the application:

## **LISTING OF CLAIMS**

- 1. (canceled)
- **2.** (currently amended) The flat display as claimed in claim [[1]] <u>16</u>, wherein the first stand is hinged on the main body.
- 3. 15. (canceled)
- 16. (new) A flat display, comprising:
  - a main body;
  - a first stand connected to the main body; and
  - a second stand, detachably connected to the first stand;
- wherein, the flat display stands on a surface by way of the main body and the first stand when the second stand is detached from the first stand, and the flat display stands on the surface only by way of the second stand when the first and second stand are connected.
- 17. (new) The flat display as claimed in claim 2, wherein when the flat display stands on the surface by way of the main body and the first stand, the main body and the first stand form a specific angle.
- **18.** (new) The flat display as claimed in claim 16, wherein the second stand comprises a flat bottom surface to stabilize the main body when the flat display stands on the surface only by way of the second stand.

USSN 10/615,168

Group No. 3632

Examiner: Marsh, Steven M.

Page 5

19. (new) The flat display as claimed in claim 16, wherein the first stand defines a hole,

and the second stand comprises an engaging portion fit into the hole to allow

connection between the first stand and the second stand.

20. (new) The flat display as claimed in claim 19, wherein the second stand further

comprises a first spring forcing the engaging portion to join the hole.

21. (new) The flat display as claimed in claim 19, wherein the second stand further

comprises a button forcing the engaging portion to separate from the hole, to detach the

second stand from the first stand.

22. (new) The flat display as claimed in claim 19, wherein the second stand further

comprises a rail inside for guiding insertion of the first stand into the second stand.

23. (new) The flat display as claimed in claim 22, wherein the second stand further

comprises a second spring disposed at a bottom of the rail to push against the first

stand when the first stand is inserted in the second stand.

24. (new) The flat display as claimed in claim 23, wherein the second stand further

comprises a button forcing the engaging portion to separate from the hole, the second

spring forcing the first stand to separate from the second stand.

25. (new) The flat display as claimed in claim 16, wherein when the flat display stands

on the surface only by way of the second stand, the main body is suspended from the

surface.

**26.** (new) A flat display comprising:

a main body;

a first stand connected to the main body; and

a second stand being hollow and detachably connected to the first stand;

USSN 10/615,168

Group No. 3632

Examiner: Marsh, Steven M.

Page 6

wherein, the flat display stands on a surface by way of the main body and the

first stand when the second stand is detached from the first stand, and the flat display

stands on the surface only by way of the second stand when the first stand is housed in

the second stand.

27. (new) The flat display as claimed in claim 26, wherein the first stand is hinged on the

main body.

28. (new) The flat display as claimed in claim 27, wherein when the flat display stands

on the surface by way of the main body and the first stand, the main body and the first

stand form a specific angle.

29. (new) The flat display as claimed in claim 26, wherein the second stand comprises a

flat bottom surface to stabilize the main body when the flat display stands on the

surface only by way of the second stand.

30. (New) The flat display as claimed in claim 26, wherein the first stand defines a hole,

and the second stand comprises an engaging portion fit in the hole to allow connection

between the first stand and the second stand.

31. (new) The flat display as claimed in claim 30, wherein the second stand further

comprises a first spring forcing the engaging portion to join in the hole.

32. (new) The flat display as claimed in claim 30, wherein the second stand further

comprises a button forcing the engaging portion to separate from the hole, to detach the

second stand from the first stand.

33. (new) The flat display as claimed in claim 30, wherein the second stand further

comprises a rail inside for guiding insertion of the first stand into the second stand.

USSN 10/615,168 Group No. 3632

Examiner: Marsh, Steven M.

Page 7

**34.** (new) The flat display as claimed in claim 33, wherein the second stand further comprises a second spring disposed at a bottom of the rail to push against the first stand when the first stand is inserted in the second stand.

35. (new) The flat display as claimed in claim 26, wherein when the flat display stands on the surface only by way of the second stand, the main body is suspended from the surface.

\* \* \*